




PRODUCT SPECIFICATION



ACRON P/N:GDI07-N3-08013

育鼎精密工業股份有限公司
ACRON PRECISION INDUSTRIAL CO., LTD

桃園縣八德市廣德里新興路 55 號
No.55, SinSing Road., Bade City, Taoyuan County 334, Taiwan(R.O.C)
TEL : 886-3-3629889 FAX : 886-3-3664917

☐ 東莞睦永電子五金廠
(AMMI)

☐ 東莞育鼎電子五金廠
(ACRON)

☒ 東莞愷興電子科技電子有限公司
(NUCONN)

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	1 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI



PRODUCT SPECIFICATION

1.0 SCOPE

This Product Specification covers the performance requirements for Vertical RJ45 with transformer connector series.

2.0 PRODUCT DESCRIPTION

2.1 PRODUCT NAME AND SERIES NUMBER(S)

Vertical RJ45 with transformer :GDI07-N3-08013

2.2 DIMENSIONS, MATERIALS, PLATINGS AND MARKINGS

See appropriate sales drawings for details on dimensions ,materials , plating and markings.

2.3 SAFETY AGENCY APPROVALS

See appropriate sales drawings

2.4 PRODUCT WEIGHT

The product weight is 5.504g

2.5 PRODUCING PLANT FACTORY AND ADDRESS

Producing plant factory: Nuconn Industry CORP

Coil plant factory: DongGuan Nuconn Industry CORP.or MinXin Electronic CORP
or Vetak Electronic CORP .

DongGuan Nuconn Industry CORP. Address:

Nr.32,RongFu Rd.,3rd Industrial District,ShangSha Village,,ChangeAn Town,DonGuan
City,GuangDong,

MinXin Electronic CORP.Address:

Qianwei City industrial park,SiChuan

Vetak Electronic CORP. Address

XinZhai Village, Sansui city , GuiZhou,

3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS

Please refer to the Sales Drawings , and other sections of this Specification for specific references to applicable documents and specifications. In cases where the Product Specification differs from the Sales Drawings, the Sales Drawing will take precedence

EIA-364 TEST METHODS FOR ELECTRICAL CONNECTORS

4.0 RATINGS

4.1 TEMPERATURE

Operating Temperature Range: 0°C to + 70°C

Storage Temperature Range: - 40°C to + 85°C

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	2 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI



PRODUCT SPECIFICATION

5.0 PERFORMANCE

Item	Test Items	Requirement	Procedures
1	Examination of Product	Meets requirements of product drawing. No physical damage.	Visual, dimensional and functional per applicable quality inspection plan.

Electrical Requirements

2	LOW Contact Resistance Level	30 mΩ max initial ΔR = 30 mΩ max final	Mate subject connector with compatible connector. EIA-364-23B
3	Insulation Resistance	1000 MΩ min initial 50 MΩ min final	Apply 100±10% Volts DC between adjacent contacts of mated connectors for one minute. EIA-364-21
4	Dielectric Withstanding Voltage	No discharge, flashover or breakdown. Current leakage: 1 mA max	For mated specimens, 2250VDC between connected RJ interface contacts and all PCB tails connected together with shield. 1 milliamp ere cutoff current, 500 Volts per second maximum ramp. EIA-364-20

Mechanical Requirements

5	Mating and Un-mating Forces	Insertion Force:22N max Unlatched Withdrawal Force: 22N max Latched Withdrawal Force: 89N min	Measure force necessary to mate and un-mate connectors using the free floating fixtures at rate of 25mm/min. EIA-364-05B
6	Solder ability	Wetting must occur over at least 95% of the solder immersion surface	Solder:SN/3.0Ag/0.5Cu,Flux:ROSIN 25%,IPA75%.High Temp Storage:150°C 1 hour, PCT: 105°C 100% 1.22*10 ⁵ Pa 4 hours. Solder 240°C±2°C; Immersion depth 2mm; Immersion time 3S
7	Terminal Strength	Appearance meet requirement	Gravitation 500g , Winding 90 angle 2-3sec
8	KOJIRI Strength	Appearance meet requirement	Left: 100N, push 15sec Right: 100N, push 15sec Up: 100N, push 15sec Down : 100N, push 15se

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	3 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI



PRODUCT SPECIFICATION



9	Solder Joint Strength Test	<p>(1) The variation must be $50\% \leq$ of the initial value</p> <p>(2) After test measured items must be $75\% \leq$ of solder (Pb/Sn) item</p>	<p>(1)Temp Cycle Test Min Temp: -40°C . MAX TEMP:+125°C TIME : Each 30 min. CYCLES:200</p> <p>(2) Measurement Item: Component with LEAD: Tension Test (EIAJED-4702); Component without LEAD: Bend Test (EIAJED-4702)</p> <p>(3) Measurement cycle: INITIAL,(100) 200</p> <p>(4) Measurement SMPL: Component with LEAD: 5LEADS\leq Component without LEAD: 5POINTS\leq To calculate Average</p>
10	Physical Shock	<p>No electrical discontinuity greater than 1μsecond. Shall meet visual requirements, and show no physical damages.</p>	<p>Subject mated connectors to 50 G's (peak value) half-sine shock pulses of 11 milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. EIA-364-27B</p>
11	Durability	<p>750 cycles with no function damage for RJ-45. Low Level Contact Resistance: $\Delta R = 30m\Omega$ max final</p>	<p>The sample should be mounted in the tester and fully mated and unmated 300 times per hour at the rate of 25mm/min. EIA-364-09C</p>
12	Random Vibration	<p>No electrical discontinuity greater than 1μsecond. Shall meet visual requirements, and show no physical damages.</p>	<p>The electrical load condition shall be 100mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency which being varied uniformly between the approximate limits of 10 and 55 Hz. The entire frequency range, from 10 to 55 Hz and return to 10 Hz, shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. EIA-364-28D</p>

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	4 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI



PRODUCT SPECIFICATION

Environment Requirements

13	Thermal Shock (Simulate Non-Operating State)	Δ R: 30m Ω max (change from initial) & Appearance: no damage	Subject mated connectors to 100 cycles between -40℃ and 85℃ , 30 minutes duration at both temperature extremes. EIA-364-32C															
14	Humidity-Temperature Cycling	Δ R: 30m Ω max (change from initial) & Appearance: no damage	Mated connectors placed in humidity chamber (Humidity 80-98%, Temperature 20-65℃) for 500 Hrs. EIA-364-31B, Method IV, Except 7a															
15	Temperature Life (Heat Aging)	Δ R: 30m Ω max (change from initial) & Appearance: no damage	Subject mated connectors to temperature life at 85℃ for 500 hours. EIA-364-17B, Method A															
16	Temperature Life (Cold Aging)	Δ R: 30m Ω max (change from initial) & Appearance: no damage	Subject mated connectors to temperature life at -40℃ for 500 hours EIA-364-17B, Method A															
17	Salt Spray	Δ R: 30m Ω max (change from initial) & Appearance: no damage	8hours moving 16hours resting total 24hours 3cycles Atmosphere: salt spray from a 5% solution. Temperature: 35 +1/-2℃ EIA 364-26															
18	Damp Heat, Steady State	JIS C 0022 JEC Pub.68 2-3 Ca MIL-STD-202 103B	Test Temp :40±2℃ Relative Humidity:90～95%RH Test time:500Hrs															
19	Change of Temperature	JIS C 0025 JEC Pub.68 2-14 NA MIL-STD-202 102A (Unless otherwise specified, either method 1 or method 2. is to be chosen)	<div><div><div>Metod1</div></div><div><div>Metod2</div></div></div> <div><p>(Both Method 1 and 2 are performed under following conditions)</p><table><tr><th>Stage</th><th>Temp</th><th>Time</th></tr><tr><td>t1</td><td>-40°</td><td>30min</td></tr><tr><td>t2</td><td>5~35℃</td><td>Less than 5min</td></tr><tr><td>t3</td><td>85°</td><td>30min</td></tr><tr><td>t4</td><td>5~35℃</td><td>Less than 5min</td></tr></table><p>Number of test cycles:100cycles</p></div>	Stage	Temp	Time	t1	-40°	30min	t2	5~35℃	Less than 5min	t3	85°	30min	t4	5~35℃	Less than 5min
Stage	Temp	Time																
t1	-40°	30min																
t2	5~35℃	Less than 5min																
t3	85°	30min																
t4	5~35℃	Less than 5min																
20	Ammonia	Appearance: no damage	Hydrogen Ion Exponent Index (PH)=10 Test Temperature:15~35℃ Test Time:72±4hrs															

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	5 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI




PRODUCT SPECIFICATION

21	Soldering Heat	1: Electrical and mechanical performance must be satisfactory in specifications 2: There must be no conspicuous changes in appearance (For example warping, swelling, cracking, indication)	MATERIALS Solder : Sn/99Ag/0.3/Cu0.7 (Weight%) If no doubts arise in judgment, it is ok to use another SOLDER TEST CONDITION 1 : TEST A: Flow Soldering (Partly Heating) 260±3°C 10S ≒ 2 : TEST B: Hand Soldering 400°C (Soldering iron tip) 3S ≒
----	----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.0 PACKAGING

Parts shall be packaged to protect against damage during handling, transit and storage. See packaging appropriate drawings

7.0 RECOMMENDED WAVE SOLDERING PROFILE




PARAMETER	REFERENCE	LEAD FREE SPECIFICATION
PREHEAT TEMPERATURE GRADIENT		+1~4°C/sec
PREHEAT TIME	t1	70 sec
PREHEAT TEMPERATURE	T1	100~120°C
SOLDER POT TEMPERATURE	T PEAK	260°C
DWELL TIME	t2	5 SEC
PEAK BOARD TOP TEMPERATURE		190°C
COOLING TEMPERATURE GRADIENT		-6°C/SEC MAX.

REVISION:	ECR/ECN INFORMATION:	PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No: DATE:	NEW SPEC. 2013/02/27	PRODUCT NAME Vertical RJ45 10/100 BASE-T	6 of 7
DOCUMENT NUMBER: PS-GD-0015		CREATED / REVISED BY: BRIAN.TAN	CHECKED BY: KENNY.CHEN	APPROVED BY: KIMI




PRODUCT SPECIFICATION


8.0 RECOMMENDED RJ PLUG SPECIFICATION



* There must be no damage to housing or locking latch. There must be no nicks or cuts in cable.



FOLLOW SPECIFICATION : FCC, PART 68, SUBPART F
FIGURE 68.500 (C)(2)(ii)



FOLLOW SPECIFICATION : FCC, PART 68,
SUBPART F FIGURE 68.500 (C)(2)(i)
AND IEC 603-7 FIGURE 23 & 24

REVISION:	ECR/ECN INFORMATION:		PRODUCT NO	GDI07-N3-08013	SHEET No
A	EC No:	NEW SPEC.	PRODUCT NAME	Vertical RJ45 10/100 BASE-T	7 of 7
	DATE:	2013/02/27			
DOCUMENT NUMBER:		CREATED / REVISED BY:		CHECKED BY:	APPROVED BY:
PS-GD-0015		BRIAN.TAN		KENNY.CHEN	KIMI